

RUST CONVERTER

Transform, Seal, & Prevent

DESCRIPTION

Rust Converter is a surface conditioner and primer that changes rust into a dark protective polymeric coating. It converts existing rust to an inert coating that seals out moisture to prevent future rust and corrosion. This black polymer coating stands up to exposure to weather, rain, sun, and salt spray without peeling or cracking. Rust Converter is an excellent primer for use under all oil-based paints.

FEATURES

- Half existing rust
- Prevents further rust
- Converts rust into an inert coating
- Excellent primer for all oil-based paints
- Seals out moisture
- Stands up to rain, sun and salt spray
- Long term protection for iron and steel
- One gallon will cover 500 sq. ft. of a smooth non-porous surface. Irregular, porous surfaces will require a heavier application rate.

HOW TO USE

- Shake or stir well before using
- Remove large rust and scale particles with a brush and clean the surface of grease and dirt
- Apply by brushing or rolling
- The coating will dry to a smooth, darkened finish in 20 minutes and will be fully cured after 24 hours
The cured Rust Converter coating should be sealed over with a high-quality oil-based paint (do not use water-based latex paints)
- No other primer is required
- Application equipment should be cleaned immediately with soap and water

SPECIFICATIONS

| | |
|--------------------------|---------------|
| Physical Form | Opaque Liquid |
| Color | Beige |
| Odor | Bland |
| Specific Gravity | 1.13 |
| Flash Point (TOC) | None |

HMIS SYMBOL

| | |
|---------------------|---|
| Health | 2 |
| Flammability | 0 |
| Reactivity | 0 |