

SEES PROOF

Anti-Seize Lubricating Compound

DESCRIPTION

Sees Proof is an anti-seize lubricating compound for use as a sealing compound on high heat, high pressure gaskets, hoses, hydraulic fitting steel, brass, aluminum, or rubber. It is used on pre-combustion chamber fuel injection nozzles, valve cages; for boiler fittings, face pate studs and man hole covers, stay bolts, stay tubes, burner assemblies, pulleys, and sprockets. Sees Proof resists fresh and salt water on all engine and deck fittings and fasteners, etc. Sees Proof's temperature-resistant formulation protects against galling, seizing, pitting, fretting, corrosion, and distortion of threaded, keyed, splined, or press-fitted assemblies. It allows tighter, more vibration-proof seals using less torque while making disassembly easier.

FEATURES

- Protects at sustained temperatures to 2100° F
- Highly resistant to moisture, weather, chemical fumes, salt spray, and steam.
- Allows tighter, more vibration-proof seals using less torque

HOW TO USE

Bulk: Pre-clean surface to be treated, removing an old contaminated grease, dirt, or grit. Brush on.

Aerosol: Spray only at temperatures above 60°F.

1. Shake can vigorously for one minute after mixing ball begins to rattle
2. Make sure surface is cleaned of all dirt, grease, and grime
3. Spray liberal amount from distance of 8-10 in
4. Invert can after use and spray short bursts to clear valve.

HMIS SYMBOL

	Aerosol	Bulk
Health	2	2
Flammability	3	0
Reactivity	0	1

SPECIFICATIONS

	Aerosol	Bulk
Physical Form	Viscous Liquid	Viscous Paste
Color	Gray	Gray
Odor	Solvent	Solvent
Specific Gravity	1.034	1.394
Flash Point (TCC)	0°F	None