

DESCRIPTION

Tri-Cool is a soluble oil coolant for machining of all steels and gives good performance with most copper alloys. To eliminate the possibility of staining, copper alloys should be cleaned after machining.

PROPERTIES

Appearance:	Light Yellow Oil
Flash Point:	285°F
Density:	7.07 lbs/gal
Viscosity:	SUS @ 100 F 30 - 33 cSt @ 40 C 12 - 14
Phosphorous:	Present
Polar Additive:	Present

FIRST-AID

Eyes: Flush with copious amounts of water for several minutes. If irritation persists, continue with water application. If after 15 minutes irritation continues, seek medical attention.

Skin: Promptly wash skin with mild soap and water.

Inhalation: Remove to fresh air. In severe cases of overexposure, such as with a fire, administer oxygen and seek medical attention.

Ingestion: Do NOT induce vomiting. Seek medical attention. Small amounts, which may enter the mouth incidental to handling, may be rinsed out with water.

HMIS SYMBOL



Health	1
Fire	1
Reactivity	0
Personal Protection	

CAUTION

Please refer to the SDS for more detailed precautionary measures, handling instructions, and emergency procedures. **KEEP OUT OF REACH OF CHILDREN.**

FIRE FIGHTING PROCEDURES: Fight as a Class B fire. Avoid breathing fumes, wear self-contained breathing apparatus.

LEAK & SPILL PROCEDURES: Eliminate all ignition sources. Contain spill at source and prevent discharges to streams and sewer systems. Pump large spills into recovery containers. Absorb small spills with absorbent material.

CONTAINER HANDLING & STORAGE: Avoid extremes of temperature in storage. Store in well ventilated dry area away from sources of ignition. Do not store in unlabeled containers. Store away from strong oxidizers.