

QUICK PATCH

Fast Cure Patch

DESCRIPTION

Quick Patch is a 2-part acrylic acrylate fast cure patch or leveling compound which is used to fill large cracks and depressions in severely damaged concrete from a thickness of 1/8" and up. It is ideal for use in heavy industrial and manufacturing areas where a tough, durable surface is required without a long cure time.

FEATURES

- Cures in one hour for pedestrian traffic, and two hours to fill specification
- Cures from -10°F to 104°F
- Excellent for freezers (available formulation to -30°F)
- 10,650 psi compression strength
- 2,556 psi flexural strength
- Repair damaged traffic areas with minimal down time
- Each kit covers approximately 1/3 cubic foot (2 quarts Part A, 31lbs. Part B)

HOW TO USE

- All oils, greases, chemical deposits, paints, adhesives, and cement surface latents must be removed. Exposed steel reinforcements should be cleaned free from rust.
- Substrate must not have a moisture content greater than 15% by volume.
- Pour contents of Part A (2-quart cans) into overpack container.
- Stir contents of Part B (31-pound bag) into Part A.
- Mix until uniform.
- For small patches, mix 5 parts by volume of part B to 1 part by volume Part A

SPECIFICATIONS

	Part A	Part B
Physical Form	Liquid	Powder
Color	Blueish	Gray
Odor	Strong, Characteristic	None
Specific Gravity	0.94	1.65
Flash Point (TOC)	50°F	None

HMIS SYMBOL

	Part A	Part B
Health	2	2
Flammability	3	0
Reactivity	2	0